

# YL-32



## STANDARD DIE SETS

| Size         | Range (mm) | Lenght |
|--------------|------------|--------|
| <b>32-10</b> | 10-13      | 55     |
| <b>32-13</b> | 13-16      | 55     |
| <b>32-16</b> | 16-19      | 55     |
| <b>32-19</b> | 19-22      | 55     |
| <b>32-22</b> | 22-26      | 55     |
| <b>32-26</b> | 26-30      | 55     |
| <b>32-30</b> | 30-34      | 75     |
| <b>32-34</b> | 34-39      | 75     |
| <b>32-39</b> | 39-45      | 75     |
| <b>32-45</b> | 45-52      | 90     |
| <b>32-52</b> | 52-57      | 90     |
| <b>32-57</b> | 57-64      | 90     |
| <b>32-64</b> | 64-69      | 100    |
| <b>32-69</b> | 69-74      | 100    |

## TECHNICAL SPECIFICATIONS

|                                           |                     |
|-------------------------------------------|---------------------|
| <b>Max hose size</b>                      | 2" 4 SP             |
| <b>Crimping force (kN):</b>               | 2200                |
| <b>Max crimping Ø (mm):</b>               | 79                  |
| <b>Max opening (mm):</b>                  | die diameter + 32   |
| <b>Standard motor:</b>                    | 3,6kW 380V 3-ph     |
| Different voltage versions available      |                     |
| <b>Control</b>                            | Digital control     |
| <b>Master dies opening / Length (mm):</b> | 132/80              |
| <b>Crimping range (mm):</b>               | 10 – 79             |
| <b>Weight (kg)</b>                        | 300 (including oil) |
| <b>Dimensions (LxWxH mm)</b>              | 600 x 480 x 1300    |
| <b>Die sets</b>                           | Standard            |
| 10-13-16-19-22-26-30-34-39-45-52-57-64-69 |                     |
| <b>Quick Change-set</b>                   | Standard            |
| <b>Foot pedal</b>                         | Standard            |
| <b>Stand for machine</b>                  | Standard            |

# DHYDRO.COM