



P32X

ELECTRIC CRIMPER FOR SERVICE


Entry level crimping machine for occasional service use and small workshops. For more demanding crimping needs please see P32NMS.

TECHNICAL DATA

Max crimping dia (mm) ¹⁾	87
Max crimping dia (inch) ¹⁾	3.43
Max crimping force (kN)	2000
Max crimping force (tonnage)	200
Cycle time 10 mm (ø) 1-phase ¹⁾	21.1
Cycle time 10 mm (ø) 3-phase ¹⁾	68.3
Hose size ID (inch)	2 (ø54)
Die set series	32
Max opening (mm) ¹⁾	+33
Max opening without dies (mm)	132
Master die DL (mm)	99/80
Master die DL (inch)	3.93/3.15
Motor Power (kW/HP)	1.5/2.2 ¹⁾ 2.0/3.0 ¹⁾
Oil tank volume	7 l

DIMENSIONS (LxWxH)

(mm) 630x321x667



¹⁾ With standard dies. Crimping range can be increased with special dies.

CONTROL

MS

OPTIONS

- Mechanical lock stop device
- Tool base with QuickChange tool
- Tool rack with QuickChange tool



Tool base and Tool rack with QuickChange-tool as an option.

DIE SET 32-SERIES

DieSetNo	Ø (mm)	L (mm)	Crimp. range (mm)
10/06/10	10	55	10.0-12.0
10/06/12	12	55	12.0-14.0
10/06/14	14	55	14.0-16.0
10/06/16	16	55	16.0-18.0
10/06/18	18	55	18.0-20.0
10/06/20	20	75	20.0-26.0
10/06/26	26	75	26.0-30.0
10/06/30	30	75	30.0-34.0
10/06/34	34	75	34.0-39.0
10/06/39	39	75	39.0-45.0
10/06/45	45	90	45.0-51.0
10/06/51	51	90	51.0-57.0
10/06/57	57	130	57.0-63.0